

Model: 484-1G

DRI-WICK DESOLDERING BRAID (SIZE ONE~SPOOL)



Dri-Wick Desoldering Braid simplifies the desoldering of printed circuit board components, posts, pots, flags, through-hole connections, pads and traces, as well as many non-PC board applications. Careful desoldering of components/parts results in preventing damage to valuable products. Stop throwing money in the trash can...salvage and repair high-value parts and products with Dri-Wick Desoldering Braid.

To insure quality and reliable service, we start with only the finest oxygen-free and oil-free fine gauge wire. Our 100% copper wick is then coated with flux, which cleans connections thoroughly during desoldering to insure maximum solderability. This thin coating of flux also provides dependable, long-lasting protection from oxidation.

FEATURES AND BENEFITS

Oxide-free clean copper wound in advanced braid design around a static dissipative spool

Pure Rosin type R flux conforming to all the requirements of MIL-F-14256 and IPC Standard-J-STD-004

50 and 500 foot rolls available upon request

APPLICATIONS

Users of this product have stated that they use it for several jobs which include but are not limited to:
1. Removing excess solder from Micro & Integrated circuits

TECHNICAL SPECIFICATIONS

ESD Safe	Yes
Braid Width	.035 in / 0.09 cm
Country of Origin	CR
RoHS Compliant	Yes
Safety Data Sheets	Download
Warranty Policy	Details

SIMILAR PRODUCTS

The following products are related (similar model but different specifications, etc.) to Model 484-1G featured on this page:

Model	Product Name
484-1	Dri-Wick Desoldering Braid (Size One~Sleeve)
484-2G	Dri-Wick Desoldering Braid (Size Two~Spool)